Date:

# Safety data sheet according to 1907/2006/EC. Article 31

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Identification de la substance:

#### **SPRAY FLAM YELLOW 600ml**

1.2 Utilisation de la substance / préparation:

## Aérosol pour projecteur de flammes sans propane ni butane

1.3 Société / entreprise: SARL Nant'Effect

4 rue de la brehannerie - 44640 Le Pellerin Siret : 8476226900020 - APE : 9002Z - RCS Nantes TVA intracom : FR93847622693 - Capital : 70000€ contact@nanteffect.fr - 0986122181

1.4 Téléphone d'urgence :

Tel.: +33(0)6 82 48 27 60

#### 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated

## 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## Hazard pictograms



Signal word: Danger

Danger

## **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 Chemical characterization: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	Dimethyl ether	25-50%
	Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas , H280	
CAS: 67-63-0	Propan-2-ol	25-50%
CE: 200-661-7 Index: 306-117-00-0	Flam. Liq. 2, H225	

Additional information: For the wording of the listed risk phrases refer to section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints. **After skin contact:** Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5. FIRE-FIGHTING MEASURES

#### 5.1 Extinguishing media

## Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

## 5.3 Advice for firefighters

Protective equipment: No special measures required.

## **6. ACCIDENTAL RELEASE MEASURES**

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

## 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

## Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e.

electric

lights. Do not pierce or burn, even after use.

## 7.2 Conditions for safe storage, including any incompatibilities

Storage:

## Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

## 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

## 115-10-6 Dimethyl ether

Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

#### 67-63-0 Propan-2-ol

Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

## General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection: Not required.

Protection of hands: Not required.

Material of gloves Not required.

Penetration time of glove material Not required.

Eye protection: Not required.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

**General Information** 

Appearance: Form: Aerosol

Colour: According to product specification

Odour: Alcohol / Characteristic Odour threshold: Not determined. pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

**Flash point:** < 0 °C (< 32 °F) Not applicable, as aerosol.

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 240 °C (464 °F)

**Decomposition temperature:** Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Explosion limits: Lower: 3.3 Vol % Upper: 26.2 Vol %

Vapour pressure at 20 °C (68 °F): 4000 hPa (3000 mm Hg)

**Density at 20 °C (68 °F):** 0.729 g/cm³ (6.084 lbs/gal)

Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not applicable.
Solubility in / Miscibility with
water: Not miscible or difficult to mix.

**Partition coefficient** 

(n-octanol/water): Not determined.

Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

Solvent content:

Organic solvents: 75.1 % EU-VOC: 547.1 g/l EU-VOC in %: 75.05 % Solids content: 24.9 %

**9.2 Other information** No further relevant information available.

#### 10. STABILITY AND REACTIVITY

## 10.1 Reactivity

## 10.2 Chemical stability

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

Acute toxicity:

#### LD/LC50 values relevant for classification:

#### 115-10-6 dimethyl ether

115 10 0 difficulty cure.		
Inhalative	CL50 / 4h	308mg/m³ (rat)
67-63-0 Propan-2-ol		
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (lapin)
Inhalative	CL50 / 4h	25000 mg/m³ (rat)

Primary irritant effect: on the skin: No irritant effect. on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

#### 12. ECOLOGICAL INFORMATION

12.1 Toxicity:

**Aquatic toxicity:** 

## 115-10-6 Dimethyl ether

EC50 / 48h > 4000 mg/l (daphnia magna)

## 67-63-0 Propan-2-ol

EC50 / 24h	9714 mg/l (daphnia magna)
CL50 / 96h	9640 mg/l (crustacean (water flea))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

## Additional ecological information:

#### General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

#### 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

## European waste catalogue

20 01 13\* solvents

15 01 04 metallic packaging

## Uncleaned packaging:

Recommendation: Non contaminated packagings may be recycled.

## 14. TRANSPORT INFORMATION

14.1 Numéro UN

ADR, IMDG, IATA UN1950

14.2 Nom d'expédition des Nations Unies

ADR 1950 Aérosols IMDG Aérosols

IATA Aérosols, flammable

14.3 Classe de danger pour le transport

## ADR:



Classe: 2 5F Gaz Etiquette: 2.1

## **IMDG, IATA:**



Classe: 2.1

Etiquette: 2.1

14.4 Packing group ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Gases.

**Danger code (Kemler): - EMS Number:** F-D,S-U

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

**Transport/Additional information:** 

**ADR** 

Limited quantities (LQ) 1L Transport category 2 Tunnel restriction code D

UN "Model Regulation": UN1950, AEROSOLS, 2.1

## 15. REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

## Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

Data compared to the previous version altered.

Cette fiche est émise par :

SARL Nant'Effect

4 rue de la brehannerie – 44640 Le Pellerin Siret :8476226900020 – APE : 9002Z – RCS Nantes TVA intracom : FR93847622693 – Capital : 70000€

contact@nanteffect.fr 0986122181

